

SHARKBITE® PEX TUBING (Continued)



Now Available in White, Blue and Red.

PEX Without Oxygen Barrier - Straight & Coils

DIAMETER	LENGTH	BLACK TEXT	RED TEXT
3/8" PEX Natural Color	100' coil	U855N100	U855NR100
	300' coil	U855N300	U855NR300
	500' coil	U855N500	U855NR500

DIAMETER	LENGTH	BLUE	RED	WHITE
1/2" PEX Blue, Red or White	5'	U860B5	U860R5	U860W5
	10'	U860B10	U860R10	U860W10
	20'	U860B20	U860R20	U860W20
	100' coil	U860B100	U860R100	U860W100
	300' coil	U860B300	U860R300	U860W300
500' coil	U860B500	U860R500	U860W500	

3/4" PEX Blue, Red or White	5'	U870B5	U870R5	U870W5
	10'	U870B10	U870R10	U870W10
	20'	U870B20	U870R20	U870W20
	100' coil	U870B100	U870R100	U870W100
	300' coil	U870B300	U870R300	U870W300
500' coil	U870B500	U870R500	U870W500	

1" PEX Blue, Red or White	5'	U880B5	U880R5	U880W5
	10'	U880B10	U880R10	U880W10
	20'	U880B20	U880R20	U880W20
	100' coil	U880B100	U880R100	U880W100
	300' coil	U880B300	U880R300	U880W300
500' coil	U880B500	U880R500	U880W500	

SHARKBITE® BARB PRODUCTS

Couplings
3/8" (UC006) 3/4" (UC016)
1/2" (UC008) 1" (UC020)

Reducing Couplings
3/8" X 1/2" (UC009) 3/4" X 1" (UC060)
1/2" X 3/4" (UC058)

Sweat Adapters
1/2" X 1/2" Fem. Sweat (UC600)
1/2" X 1/2" Male Sweat (UC607)
3/4" X 3/4" Fem. Sweat (UC606)
3/4" X 3/4" Male Sweat (UC608)
1" X 1" Male Sweat (UC609)

Threaded Adapters
1/2" X 1/2" MNPT (UC120)

Elbows
3/8" (UC246) 3/4" (UC256)
1/2" (UC248) 1" (UC260)

Reducing Elbow
1/2" X 3/4" (UC274)

Drop Ear Elbow
1/2" X 1/2" FNPT (UC334)

Tees
3/8" (UC360) 3/4" (UC370)
1/2" (UC362) 1" (UC374)

Reducing Tees
3/4" X 3/4" X 1/2" (UC412)
3/4" X 1/2" X 3/4" (UC444)
3/4" X 1/2" X 1/2" (UC454)
1" X 3/4" X 3/4" (UC414)
1" X 1" X 3/4" (UC416)

Copper Barb Manifolds
3/4" X Closed, with three 1/2" barb branches (22783)
3/4" X 3/4", with three 1/2" barb branches (22784)
3/4" X Closed, with four 1/2" barb branches (22785)
3/4" X 3/4", with four 1/2" barb branches (22786)
3/4" X Closed, with six 1/2" barb branches (22787)
3/4" X 3/4", with six 1/2" barb branches (22788)
3/4" X Closed, with eight 1/2" barb branches (22789)
3/4" X 3/4", with eight 1/2" barb branches (22790)

Copper Stubout Elbow
4" X 8" Elbow - 1/2" Barb X Closed (22791)


Regulators With PEX/Barb Ends
3/4" EB-45 (22798-0045)
1" EB-45 (22799-0045)
3/4" EB-25 (22865-0045)
3/4" EB-25-400 (22866-0045)
1" EB-25 (22867-0045)
1" EB-25-400 (22868-0045)
3/4" EB-35 (22364-0045)
1" EB-35 (22365-0045)

Clamp Rings
3/8" (UC952) 3/4" (UC955)
1/2" (UC953) 1" (UC956)

PEX Clamping Tool (UC961)
Ergonomic design for one-hand operation. For use with SharkBite® Barb 3/8", 1/2", 3/4" and 1" fittings and SharkBite® PEX tubing.

PEX Tubing Cutter (U701)
For use with SharkBite® Barb 3/8", 1/2", 3/4" and 1" SharkBite® PEX tubing.

TYPICAL SHARKBITE® APPLICATIONS



INSTALLATION AND DISCONNECTION



NEW CONSTRUCTION
Cut. Push. Done. The SharkBite® Connection System is the fastest, easiest way to plumb any residential or commercial job.

WET OR DRY REPAIRS
There's no faster way to make a repair – wet or dry. You can connect copper, CPVC or PEX pipe in any combination.

WATER HEATERS, VALVES AND MORE
Connect a water heater or shower valve. Install a mixing valve or pressure regulator – it's all a breeze with SharkBite® push-fit connections.

HYDRONIC HEATING SYSTEMS
Under the floor or behind a wall, a broad range of SharkBite® push-fit fittings and PEX products gives you confident connections.

EASY INSTALLATION
Ensure the pipe is cut square and rough edges and debris are removed. Mark pipe for 1" depth. Push pipe and fitting together.

FAST DISASSEMBLY
Using the simple disconnect tool, fittings can be easily changed and reused.

CERTIFICATIONS

The SharkBite® push-fit fittings have been design certified and listed to ASSE 1061/NSF 61. The SharkBite® push-fit fittings are listed by IAPMO and are certified for potable and hydronic heating water distribution (note: Glycol mixture for hydronics is not to exceed 50% concentration). The SharkBite® push-fit fittings have been certified for underground applications and as a manufactured joint without access panels and they meet UPC, IPC and cUPC requirements.

Please consult with local plumbing codes concerning specific applications. The SharkBite® tubing without oxygen barrier is approved for all model codes in the US and Canada for use in hydronic and potable water systems and is certified to the following standards: NSF 14/61, NSF P171, ASTM F 876, ASTM F 877, CSA B137.5 and AWWA C904.

The SharkBite® tubing with oxygen barrier is approved for use in all model codes in the US and Canada for use in hydronic and potable water systems and is certified to the following standards: NSF 14/61, NSF P171, ASTM F 876, ASTM F 877, CSA B137.5 and AWWA C904.

SHARKBITE® PEX INSIDE (ID) & OUTSIDE DIAMETER (OD)

Nominal Diameter	OD inches	ID inches
3/8"	0.5	0.35
1/2"	0.625	0.475
3/4"	0.875	0.671
1"	1.125	0.885



OVERBUILT IS AN UNDERSTATEMENT.®

2400 7th Avenue SW
Cullman, AL 35055-0278
1-877-700-4242
FAX: 1-877-700-4280
www.cashacme.com

In Canada Contact:
1-888-820-0120
FAX: 1-888-820-0121
www.cashacme.ca



A Division of the Reliance Worldwide Corporation

09-CAC-109 4.16.09 Printed in USA



LIGHTNING FAST. WON'T LET GO.

