
The Conserver[™] Dual Flush HET






The Conserver™ **Dual Flush HET**







Dimensions may vary (+) or (-) 1/4". Dimensions shown in parentheses are in millimeters: 25.4 mm = 1 inch. Note: Fixture dimensions are nominal and conform with dimension and performance requirements of ASME/ANSI Standards A112.19.2M. PSI rating: 20 minimum to 80 maximum per ASME A112.19.2. Dimensions subject to change or cancellation without notice. Briggs is not responsible for the use of superseded or voided specification information.

FEATURES

- High-efficiency toilet (HET)
- Choose either 1.6 or 1.0 gpf*
- Wide 2" glazed trapway
- Top-mounted push button flush release
- Stain-resistant vitreous china
- 18" x 10" footprint, Model 4207
- 20-1/2" x 10" footprint, Model 4208
- Limited lifetime warranty
- * Estimated average consumption of 1.28 gpf

AVAILABLE COLORS



WHITE (130)

SPECIFICATIONS

- Model 4207: 12" rough-in round toilet, 69 lb, consists of bowl (Model 4370) and tank (Model 4484)
- Model 4208: 12" rough-in elongated toilet, 72 lb, consists of bowl (Model 4375) and tank (Model 4484)
- Model 7484: Tank lid for Model 4484, 10 lb

INSTALLATION

Installation instructions supplied

	4207	4208
A	26 3/8" (670)	28 3/8" (720)
В	16 1/2" (420)	18 1/2" (470)
С	14 1/8" (360)	14 3/8" (365)

